



Brikko

IP68 LED signal lighting fixtures

Focus on the range

Low **profile**

Extra thick glass

The new frontier of **floor integrated** lighting is supported by the small **LED source**.

Available in five different colours for different **signalling** or **set-tings**, it is characterised by its **limited thickness** which also makes it easy to install indoors.

Body: **tempered glass** diffuser on an **acid-treated metacrylate** sheet base. Rear reflector in high reflectance **specular aluminium**.

Sources: **high intensity central LED** with side emission.


Emissions: light **diffusing** emission.

Control gears: operating at **12v d.c.** with internal current **stabilising** circuit.

Accessories: control gears available separately.


Colours: translucent.

LED signal lighting fixtures IP68 **Brikko**



LIGHT BY
LUXEON

static load **1,000 Kg**
maximum transit speed **30 Km/h**
protection against impacts **IK = 9**



white LED 3.6W 12v d.c.
fixture without control gear
fixture 100x100mm 76920.00
control gear _____

amber LED 3.6W 12v d.c.
fixture without control gear
fixture 100x100mm 76922.00
control gear _____

blue LED 3.6W 12v d.c.
fixture without control gear
fixture 100x100mm 76921.00
control gear _____

green LED 3.6W 12v d.c.
fixture without control gear
fixture 100x100mm 76924.00
control gear _____

red LED 3.6W 12v d.c.
fixture without control gear
fixture 100x100mm 76925.00
control gear _____



accessories



electronic control gear IP40
230/12v d.c. 15W

38919.00

Dimensions:
130x40x30 mm

it can control up to 4
Brikko fixtures



electromagnetic control gear IP65
230/12v d.c. 50W

38920.00

**other powers
on request**

Dimensions:
110x110x45 mm

it can control up to 14
Brikko fixtures

